



LinePilot



- Central Control Interface for Extruder Ctrl
- Layer Ratio: Visualize & adjust set point % of each layer (Max 3)
- Stop, start, ramp each individual & all extruders together
- Auto / manual control functionality
- Visualize current throughput of each layer
- Visualize status of each unit on line (OK or in Alarm)
- Set & Visualize current running recipe on each gravimetric

LinePilot; Display Specifications:

- Power Panel T30, 10.1", landscape format.
- CPU and memory:
 - 600 MHz (ARM Cortex A8),
 - 512 MB onboard flash drive.
- Display and touch screen:
 - 10.1", 1024 x 600 (WSVGA) resolution,
 - analog resistive touch screen,
 - landscape format, anthracite gray pinstripe.
- Interfaces:
 - 2x Ethernet 10/100 Mbit/s (integrated switch),
 - 2x USB 2.0.
- Client software:
 - embedded service page,
 - embedded web browser.



PERFECTION IN AUTOMATION
A MEMBER OF THE ABB GROUP



LinePilot; PLC Specifications:

- X20 Compact-S CPU,
- ARM Cortex A9-500,
- 256 MByte DDR3 RAM, 32 kByte FRAM,
- 1 GByte Flash Drive on board,
- 2 USB ports,
- 1 RS232 interface,
- 1 POWERLINK interface,
- 1 Ethernet port 10/100 Base-T



PERFECTION IN AUTOMATION
A MEMBER OF THE ABB GROUP

